

**Floorstanding Cistern
UNIVERSAL
82866.1**



TECHNICAL DATA

Order no.	82866.1	Mounting acc. incl.	Charge 731 – corner valve for rear water inlet (3/8"-1/2") and water inlet pipe
Certified to	DIN 19542		Charge 735 – corner valve for rear water inlet (1/2"-1/2") and water inlet pipe (AUS)
matching for	Floorstanding WC pan Mimo by Laufen, order no. 82155.1 Lb3, order no. 82168.4 Laufen Pro, order no. 82295.2 Kartell by Laufen, order no. 82333.1 Palace, order no. 82370.1 Palomba Collection, order no. 82380.6	Colours	see colour table
Specification	floorstanding Flushing mechanism Typ 720, Charge 731 water condensation insulation Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)	SPECIFICATION TEXT Floorstanding cistern UNIVERSAL, sanitary ceramic, DIN 19542, dimensions 400/410 x 140 x 980 mm, Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush), concealed water inlet top left rear (1/2") matching floorstanding WC pan, Mimo by Laufen order no. 82155.1, Lb3 order no. 82168.4, Laufen Pro order no. 82295.2, Kartell by Laufen order no. 82333.1, Palace order no. 82370.1, Palomba Collection order no. 82380.6 Special feature: water condensation insulation Further options: Surface refinement LCC (only white), Australian Standard option 735	
Special specification	Australian Standard, Charge 735 (4,5/3-l-flush)		Order no. 82866.1
Water inlet	concealed top left rear 1/2"		
Weight	30,0 kg		

TECHNICAL DRAWINGS / S 1 : 20

